

SAFETY DATA SHEET

POLISEL CELLULOSIC THINNER

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.
Commission Regulation (EU) 2020/878 of 18 June 2020.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name POLISEL CELLULOSIC THINNER

Product number 9380020

Container size 0,9 L, 3 L, 12 L, 12 KG, 15 L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses It can be used at thinning cellulosic products and in cleaning application tools.

1.3. Details of the supplier of the safety data sheet

1.4. Emergency telephone number

Emergency telephone ULUSAL ZEHIR DANISMA MERKEZI(UZEM):114 POLISAN KANSAI BOYA SAN. TİC. A.Ş. : +90 262 679 73 45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Repr. 2 - H361d STOT RE 2 - H373

Environmental hazards Not Classified

Classification (Regulation (EC)
No. 1272/2008 CLP).

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

POLISEL CELLULOSIC THINNER

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe vapour/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P310 Immediately call a POISON CENTER/ doctor.
 P314 Get medical advice/ attention if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

TOLUENE, 2-methylpropan-1-ol

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

toluene		60-80%
CAS number: 108-88-3		EC number: 203-625-9
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304		
ACETONE		10-20%
CAS number: 67-64-1		EC number: 200-662-2
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

POLISEL CELLULOSIC THINNER

xylene		10-20%
CAS number: 1330-20-7	EC number: 215-535-7	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		
2-BUTOXYETHANOL		5-10%
CAS number: 111-76-2	EC number: 203-905-0	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		
BUTYL ACETATE -norm		5-10%
CAS number: 123-86-4	EC number: 204-658-1	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336		
2-methylpropan-1-ol		1-5%
CAS number: 78-83-1	EC number: 201-148-0	
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	If in doubt, get medical attention promptly. Get medical attention if symptoms are severe or persist. Never give anything by mouth to an unconscious person. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air at once. Get medical attention. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Remove affected person from source of contamination. Give plenty of water to drink. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

POLISEL CELLULOSIC THINNER

4.2. Most important symptoms and effects, both acute and delayed

General information	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep affected person warm and at rest. Do not induce vomiting.
Skin contact	Skin irritation. Harmful to health in contact with skin.
Eye contact	Irritation, burning, lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known.
Hazardous combustion products	Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting	Contain and collect extinguishing water.
Special protective equipment for firefighters	Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.
For non-emergency personnel	No data available.
For emergency responders	No data available.

6.2. Environmental precautions

Environmental precautions	Avoid or minimise the creation of any environmental contamination. Contain spillage with sand, earth or other suitable non-combustible material.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with skin and eyes.
--------------------------	---

POLISEL CELLULOSIC THINNER

Advice on general occupational hygiene

When using do not eat, drink or smoke. Do not smoke in work area. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Usage description

Use the product according to its Technical Data Sheet or instructions written on the label.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

toluene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk, BMGV

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk)

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

2-methylpropan-1-ol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

BMGV = Biological monitoring guidance value.

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Personal protection

Use the personal protective equipments showed above. Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

POLISEL CELLULOSIC THINNER

Hand protection	Use protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Thermal hazards	No data available.
Environmental exposure controls	Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Colourless liquid.
Odour	Characteristic.
Flash point	-7,5°C

9.2. Other information

Refractive index	1,4770-1,4670
-------------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No potentially hazardous reactions known.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat. Avoid contact with the following materials: Oxidising agents. Reducing agents.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Keep away from flammable and combustible materials.
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral	
ATE oral (mg/kg)	7,142.86
Acute toxicity - dermal	
ATE dermal (mg/kg)	6,470.59

POLISEL CELLULOSIC THINNER

Acute toxicity - inhalation

ATE inhalation (gases ppm) 26,470.59

ATE inhalation (vapours mg/l) 64.71

ATE inhalation (dusts/mists mg/l) 8.82

Acute and chronic health hazards Inhalation May cause respiratory system irritation. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. SKIN CONTACT. Irritating to skin. Product has a defatting effect on skin. EYE CONTACT. Irritating to eyes. INGESTION. May cause discomfort.

11.2 Information on other hazards

Information on other hazards

Toxicological information on ingredients.

toluene

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability No data available

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6 Endocrine disrupting properties

Endocrine disrupting properties

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN number or ID number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

POLISEL CELLULOSIC THINNER

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number
(ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

POLISEL CELLULOSIC THINNER

Guidance

Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.
CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment**SECTION 16: Other information****General information**

This safety data sheet information was prepared as a requirement of Chemical Substances Regulations. Product 1 Chapter gives other than those specified. Utilization of the product are beyond our control to special conditions, the supplier, the consumer is responsible for ensuring that the requirements of legislation on the subject. Information consisting of present-day situation in this safety data sheet are based on national legislation, health, safety and environmental respects the way. Technical performance and does not guarantee suitability for specific situations. Based on our present knowledge projects, but they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Issued by

Emre ÇELİK/ Sertifika Numarası: KDU01.16.11 / Belge Tarihi: 12.04.2021

Revision date

15/12/2023

Revision

02

Supersedes date

28/02/2017

SDS number

20725

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Signature

Emre ÇELİK/Sertifika Numarası: KDU01.16.11/Belge Tarihi: 12.04.2021

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.