



## PRIMERA SYNTHETIC PRIMER

### TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

Alkyd based, synthetic primer.

### PRODUCT FEATURES

- Easy to apply
- Brush mark-free
- Creates a smooth and durable layer under topcoat paints
- Strong adhesive

### RECOMMENDED FOR

It is used for wood, chipboard, metal and plaster surfaces.

#### Drying time

Touch dry	2-3	h
Recoat	6-8	h
Full dry	8-10	h

\* The provided drying time data are available in 23 °C ambient temperature and 50 ± 2 % relative humidity conditions.

### SURFACE

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting.

#### Other Surfaces

On wooden surfaces; The knots are cleaned, any old paint is scraped off, sanded.  
Surfaces that need repair; It is puttied with SUPER PASTE.



## PRIMERA SYNTHETIC PRIMER

### TECHNICAL DATA SHEET

#### APPLICATION

It can be applied 1 or 2 coats. 6-8 hours should be allowed between coats. If second coat would be applied after 48 hours, sanding is necessary for good adhesion to the surface. If Synthetic Primer drying is not completed top coat synthetic paint should not be applied due to reduction of its gloss. Use Synthetic Thinner as thinner

Application Temperature (°C)	: min +5 °C / max + 30 °C
Thinning Ratio (%)	: For Brush&Roller 5-10%, Spray 10-15%
Consumption (m <sup>2</sup> / L)	: 13-15 (For single coat)

#### Application Equipment

Brush	Applicable
Roller	Applicable
Spray	Applicable

#### TS CLASSIFICATION

TSE to 39 is appropriate and has the TSE.

#### POZ No.

#### STORAGE and PACKAGING

Packaging	0,75 L, 2,5 L, 10 KG, 20 KG
Storage Conditions	In sealed packaging, store in a cool place.
Shelf life	3 years

#### HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.  
Product of the safety data sheet should be treated by the rules.  
Refer to the nearest health facility for unexpected health problems.

#### LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.