

ŞEFFAF JEL ASTAR

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Water based, acrylic based, ready-to-use clear interior primer developed to prevent surface defects and glassy appearance that may occur due to the use of unfilled primers on plaster surfaces.

FEATURES

- Easy to apply, easy to spread.
- Reduces surface absorbency.
- Perfectly penetrates the surface and fills it evenly.
- Does not splash or drip.

RECOMMENDED FOR

- It can be applied on plaster, plasterboard surfaces and putty on interior walls.

SURFACE PREPARATION

The application surfaces must be cleaned of dust and dirt. The surface and ambient temperature during application should be between 5-30°C.

APPLICATION

Apply on satin plaster surfaces which are to be painted for the first time without thinning. Ensures good adherence by allowing the paint to spread homogeneously on the surface. It is important to apply in a single coat and avoid overlapping on joints. In such case the primer may have a glazy look and lead to issues like spreading over the top coat. Stir before use.

Application Features

Thinning Ratio	Ready to use.
Application Temperature (°C)	5-30
Coverage (m ² /L)	15-20

Application Equipment

Applied with brush or roller.

ŞEFFAF JEL ASTAR

TECHNICAL DATA SHEET

Drying Time (20 °C)

Touch dry (min)	30
Full dry (h)	3-4

* The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.

Poz No

STORAGE and PACKAGING

Packaging Information	2.5 L, 15 L
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Kansai Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.